

GT250E Grid Tie Inverter



The Xantrex GT250E Grid Tie Inverter is based on a reliable platform that is used in grid-connected photovoltaic and wind turbine applications in North America and Europe. Easy to install and operate, the GT250E automates startup and shutdown. It incorporates advanced Maximum Power Point Tracking (MPPT) technology to maximize the energy harvested from a PV array. To minimize power losses during the conversion process, the inverter's switching technology uses insulated gate bi-polar transistors. Multiple inverters can be paralleled for large power installations. Designed for European PV installations, the GT250E is compliant to applicable European directives.

Features

- ▶ Digital Signal Processor (DSP) based controls with self-diagnostics
- ▶ LCD display with keypad for display of operating status and for access of user-changeable settings
- ▶ Inverter shut-off and disconnects
- ▶ Over- and under-voltage and frequency protection, shutting down the inverter
- ▶ Anti-islanding protection prevents back-feeding inverter generated power to the grid in the event of a utility outage
- ▶ User definable power tracking allows the user to match the inverter to the array, as well as to adjust delay periods to customize system shutdown sequences
- ▶ Isolation protection
- ▶ DC and AC over voltage protection
- ▶ Graphical user interface software for real time communications, monitoring, and control

Options

- ▶ Remote monitoring and fault notification via telephone modem or web server
- ▶ Data acquisition and logging
- ▶ Warranty extensions

Xantrex Technology Inc.

Headquarters

8999 Nelson Way
Burnaby, British Columbia
Canada V5A 4B5
+1 800 670 0707 Toll Free
+1 604 420 1591 Fax

Europe

Xantrex Technology GmbH
Steinheimer Str. 117
63500 Seligenstadt
Germany
+49 (0) 6182 81 6000 Tel
+49 (0) 6182 81 6001 Fax

Xantrex Technology S.L.
Bac de Roda, 52 edificio A
08019 Barcelona
Spain
+34 93 433 8350 Tel
+34 93 433 8351 Fax

europesales@xantrex.com



Our evolution to Schneider Electric, the global specialist in energy management, re-affirms our commitment to provide you with innovative solutions, best-in-class customer service, and exceptional quality in everything we do. We are proud to be your partner, and we are dedicated to helping you make the most of your energy.

www.xantrex.com

250 kW Three-Phase Inverter

Electrical Specifications

Nominal power rating (AC)	250 kW AC
Nominal AC voltage	315 VAC three phase (other voltage levels on request)
Nominal AC frequency	50 Hz (60 Hz on request)
Line power factor	> 0,99 above 20% rated power
AC current distortion	< 3% THD at rated power
Max AC line current	460 A
Stand-by tare losses	<100 W
Night consumption	<100 W
Min DC voltage for feed-in	450 VDC
Max DC current	555 Adc
Max open circuit voltage	880 VDC
Power Tracking window range	450 to 800 VDC
Max efficiency	97,5%
European efficiency	96,6%

General Specifications

Ambient temperature range	- 10° to 45°C
Enclosure environmental rating	IP21
Enclosure	Rittal TS Series
Weight	1160 kg
Dimensions (H x W x D)	211,2 x 200,6 x 60,5 cm
Altitude	up to 1500 m without de-rating
Relative humidity	0 to 95% non-condensing

Features & Options

Cooling method	Forced convection cooling
Protective functions	AC over / under voltage, AC over / under frequency, over temperature, AC and DC over current, DC over voltage
User display standard	LCD, four-line, 20-character with keypad
Disconnects (AC & DC)	Integral to inverter assembly
Communications software	Graphical user interface software for real time communications and control
Data acquisition and logging	Adjustable
Combiner Boxes	Optional feature (information on request)
Container solution	Optional feature (information on request)

Approvals & Safety

The GT250E complies with applicable European Directives

The GT250E complies with the requirements of VDEW

Note: Specifications subject to change without notice